

List of items likely to be procured in the next 3-5 years

Note:

1. This list may change from time to time depending on project requirements.
2. Detailed specifications will be available at the time of raising the indent.

S. No.	Title of Item	Short description
1.	Calorimeter	Manufacturing, assembly, testing and supply of calorimeter with overall height of ~ 2.5m). Involved HTEs (with length of ~400mm) manufactured from CuCrZr and involving EBW welding.
2.	Diagnostic neutral beam Vessel	Manufacturing, assembly, testing and supply of SS rectangular vacuum vessel, size: ~8.5m x 5m x 5m. SIC-1 and RCC-MR class manufacturing with all vacuum boundary weld joints designed for full penetration and 100% volumetrically examinable.
3.	Diagnostic neutral beam DDL	Manufacturing, assembly, testing and supply of Drift Duct Linear with diameter of ~1.2m and length of ~1.2 m. Vacuum brazed copper panels in circular shape, to be installed on the inner size of DD Bellow.
4.	Diagnostic neutral beam PMS	Manufacturing, assembly, testing and supply of Passive Magnetic shield with overall envelop size ~9m x ~5m x 5m for vessel PMS and ~5.4m x 4m x4m for Bushing PMS). Structural component with large number of MS plates (individual plate size ~2m x 5m x 50mmthk), to be assembled with the support structure through fastners connection.
5.	Diagnostic neutral beam ACCC	Manufacturing, assembly, testing and supply of Copper coil with size ~2.5m x 5m. Uncooled Copper coils, manufactured in rectangular shape
6.	Diagnostic neutral beam Hydraulic lines	Tools required for assembly of injectors
7.	Diagnostic neutral beam Gas feed lines	Hardwares like hydraulic pipes and gas feed lines, electrical interfaces, bellows, RF lines etc
8.	Diagnostic neutral beam Assembly tooling	
9.	Diagnostic neutral beam Interface between High Voltage Bushing and Transmission Line.	Man power supply (Welder, fitter, Fabricator etc) for integration of INTF components

10.	Diagnostic neutral beam Assembly and integration	Manufacturing, assembly, testing and supply. Standard catalogue components
11.	Diagnostic neutral beam Installation and assembly contract	Man power supply (Welder, fitter, Fabricator etc) for integration of INTF components
12.	Diagnostic neutral beam Water cooling systems additional equipments (Pumps, Tank and water)	Manufacturing, assembly, testing and supply. Standard catalogue components
13.	Diagnostic neutral beam Cryoline Dewar and auxiliary items	Manufacturing, assembly, testing and supply. Standard catalogue components with the line routing as per design
14.	Heating Neutral Beam - 3 Vessel	Manufacturing, assembly, testing and supply of Rectangular vacuum vessel made in two part (Part 1 BLV with size of ~10m x 5m x 5m and Part 2 BSV with size of ~5m x 5.5m x 6m), and then to be integrated through welding at IO site. SIC-1 and RCC-MR class manufacturing with all vacuum boundary weld joints designed for full penetration and 100% volumetrically examinable.
15.	Connecting Duct Linear	Manufacturing, assembly, testing and supply of Connecting duct linear. CuCrZr Panel (size ~3m x 1.8m x 45 mmthk) with deep drilling and EBW
16.	Duct Liner (3 Nos.)	Manufacturing, assembly, testing and supply of Duct liner with overall size of ~ 5m x 2m x 1m. RCC-MR / ASME class manufacturing involving large SS structure and several CuCrZr panels. Tech. like EBW, Exp cladding, high thk welding, Deep drilling etc
17.	Diagnostic neutral beam Exit scraper	Manufacturing, assembly, testing and supply of Exit scraper with overall height of ~2m . To be manufactured from CuOF panels (size of ~1.5m x 1m) involving the deep drilling, ED / brazing and EB welding.
18.	High Voltage Bushing	Manufacturing, assembly, testing and supply of 100kV high voltage bushing with overall diameter of ~1.5m. PIC component, involving metallic and non-metallic materials like large size Ceramic ring (along with its brazing with Kovar), FRP ring (along with its connection with SS), complex assembly of piping, Electrical, RF, Diagnostic feed throughs.
19.	Diagnostic neutral beam Drift Duct Bellow	Manufacturing, assembly, testing and supply Drift Duct bellow, double walled with diameter of ~2m. RCC-MR / EN class double walled large size bellow, with stringent requirements on the movements, manufacturing design,

		welding configurations and fatigue testing requirements
20.	Cryogenic temperature sensors (RTD type - CERNOX and PT-100)	To measure temperature at liquid helium and liquid nitrogen
21.	Temperature sensor (Carbon-Ceramic Type)	to measure temperature Spares as required for cryogenic lab activities. Equivalent product in India is not available
22.	Temperature transmitters	To transmit the temperature values to PLC. Spares as required for cryogenic lab activities. Equivalent product in India is not available
23.	Cryogenic accessories (Tapes etc.)	Special tapes for cryogenic insulation. Product may be available in India now, to be checked.
24.	Mass flow meters (Orifice / Venturi / Coriolis type)	to measure mass flow at cryogenic temperature conditions with flow range (0 to 300 g/s)
25.	Thermal mass flow meter	to measure the gas flow at room temperature conditions (300K)
26.	Control valve positioner	electro pneumatic type to regulate or manipulate the flow of fluids, such as gas through the control valve
27.	Control valve positioner	electro pneumatic type to regulate or manipulate the flow of fluids, such as gas through the control valve
28.	Dewar Level probe and transmitter	superconducting type (to measure liquid helium inside the Dewar and transmit the value to PLC)
29.	Oil separator 1 Level	to measure oil level
30.	Instr. Air Service Unit Pressure	for instrument air service
31.	Vacuum gauge	to measure the vacuum pressure
32.	Pressure transmitter	to measure pressure and transmit the value to PLC
33.	Dewar heater cartridge temperature	to measure heater temperature during liquid helium warm-up
34.	softwares	Simatic manager, CFC, graph, WINCC SCADA, for software development
35.	PLC and its spares	PLC CPU and CP and IO modules for software development
36.	Control valves	bellow sealed control valve (equal percentage type) for helium gas service (in cryogenics temperature).
37.	Vacuum pump and Helium leak detector spare parts	to evacuate the chamber and to find the leak in chamber or system

38.	Multi layer insulation (MLI)	to reduce radiation heat load at cryogenic temperature.
39.	Pressure transmitter	to measure pressure and transmit the value to PLC
40.	Cryocooler (GM type - 2 stage)	For experiments at 4K temperature
41.	Arc-4 with cable	To detect arcs in the RF amplifiers and transmission lines
42.	Cables for IO compatible	To connect different sub-systems with the control and monitoring unit
43.	Solid State Power Amplifier (18 Nos.)	As a pre-driver in RF amplifier chain
44.	3dB Combiner (9Nos.)	To combined 1.5 MW RF outputs from the two RF chains
45.	200kW Dummy Load for 3dB combiner (9Nos)	To absorb the RF power, if any at the isolated port of the 3dB combiner
46.	Fast Controller PC	To use in Local control and monitoring unit
47.	Field Programmable Gate Array based RF measurement & control board development	Development of alternate method for RF measurement & control of an RF source
48.	PLC with I/O board	To use in Local control and monitoring unit
49.	Motor & controller with accessories	To use in RF amplifier & Local control and monitoring unit
50.	SARAL Rack	To use in Local control and monitoring unit
51.	PXI & cRIO system with I/O board	To use in Local control and monitoring unit
52.	Multi core Fiber optic cable	For interfacing Field signal with LCU
53.	RF synthesizer & other RF component	Use as signal source to drive amplifier chain
54.	Cavity components for driver stage amplifier HPA2	Driver amplifier of the RF chain
55.	Co-axial Transmission line components like St. lines, Bends, Gas barriers, Directional Couplers,	Interconnection of various sub-systems of the RF source
56.	Water cooling main header line	Each Rf source has one water cooling main header line
57.	Base Frame, support frame and service platform with ladder	Each RF source has main base frame and support structure
58.	Dual channel RF power meters along with power sensors for each channel	To monitor forward and reflected power of each stage of high power amplifiers in an RF source at ITER-India & IO site
59.	Vector Network Analyser (VNA) Table Top	To measure S parameters of the RF components/Amplifiers in the Lab
60.	Vector Network Analyser (VNA) Hand held	To measure S parameters of the RF components/RF Amplifiers in the field
61.	Spectrum Analyser Table top	To measure Harmonics & Spurious of the RF Amplifiers in the lab
62.	Arbitrary waveform generators	To check the RF performance of the components, drive to RF Amplifiers during performance check in the lab

63.	RF componets i.e. low power DL for DC, Attenuaters, Phase shifters, RF switches, Power dividers, 1x5 Splitters, 1x2 splitters	to be in RF Sources for measurement, control and monitoring at low power level in each RF chain of amplifiers
64.	Auxiliarry DC Power supplies for SG, CG & filament for HPA2 & HPA3 along with additional protection & monitoring circuit for each chain	To bias HPA2 & HPA3 electrodes as per requirement in each RF chain of Amplifiers
65.	LT distribution for RF Source	To provide electical power for RF source
66.	Electrical Mesuring Equipments/Instruments i.e. Digital Oscilloscopes	To be used in measurements of parameters related to power supplies and RF amplifiers
67.	Measurement Links	Measurement of analogue parameters with optical isolation
68.	Transmission Line	Transmission of multiple power lines for few hundred meters
69.	High Voltage Deck	High voltage platform
70.	Signal Conditioning Unit Bins	Signal conditioning units for electrical to optical and optical to electrical digital signal converters- 130 channels in one bin
71.	Ion Cyclotron High Voltage Power Supply	High voltage power supply
72.	Electron Cyclotron Main High Voltage Power Supply	High voltage power supply
73.	DIAGNOSTIC NEUTRAL BEAM EGPS	High voltage power supply
74.	200kW RF Generator	1MHz power source
75.	Insulating Transformer	22/6..6kV, 5MVA
76.	Distribution Panel 6.6 KV	6.6kV class vaccum circuit breakers (CBs) switchboards for indoor use with 1 incomer and 4 outgoing configuration with accessories complete inclduing CT, PT, protection relays and instrumentation. Compliance standard ; IEC 612271
77.	Distribution Panel 400V	415V class,air circuit breaker (ACB) and miniature circuit breaker (MCB) Distribution board, four standing type, indoor use with 2 incommer and 14 outgoing with all accessories. Compliance stanadr : IEC 61439
78.	Cooling manifold with control & measurement instrumentation	Not available
79.	Aluminium Profile based support structures with Lead sheilds	Not available
80.	Oil Tank with HV sockets & accessories	Not available
81.	Arc detector system	Not available
82.	RF radiation safety detectors/monitors (170 GHz)	Not available
83.	Design of piping in valve room	Design of piping & supports within valve room with updated requirements
84.	Supply of piping & supports in valve room	Fabrication of piping spools and support structures

85.	AMC for HVAC System HIGH Side- 3 nos chillers	-
86.	AMC for EOT cranes - 5 nos.	-
87.	AMC for Domestic unit- A/C, WC, WD, etc.	-
88.	AMC for FIRE Hydrant System	-
89.	AMC for FIRE Fire Alarm system	-
90.	AMC for Fire Extinguishers	-
91.	AMC for Elevators	-
92.	AMC for Deisel Generator Set	-
93.	HCI Server Hardware	Servers
94.	VM WARE SOFTWARE and other softwares	Software
95.	ROUTERS	Routers
96.	Microsoft softwares	Softwares
97.	Backup Unit	Backup devices
98.	AIO Dektop and laptop	Hardware
99.	Workstations	Hardware
100.	Internet lease line and point to point Lease line	Internet services
101.	AMC of software, servers and application	-
102.	Fire wall	software
103.	VM WARE SOFTWARE and other software	
104.	Three simultaneous wavelength channel High Etendue Spectrometer (HES) (Quantity-Five)	Three simultaneous wavelength channel High Etendue Spectrometer (HES) (Quantity-Five)
105.	CCD/CMOS Detectors for the High Etendue Spectrometer (HES) (Quantity-Fifteen)	CCD/CMOS Detectors for the High Etendue Spectrometer (HES) (Quantity-Fifteen)
106.	Alignment system (used to align the fiber bundle head with the image plane for efficient light coupling)(Quantity-One)	Alignment system (used to align the fiber bundle head with the image plane for efficient light coupling)(Quantity-One)
107.	Optical Fiber bundle Assembly (Compatible with ITER Radiation environment)(Quantity-Five)	Optical Fiber bundle Assembly (Compatible with ITER Radiation environment)(Quantity-Five)
108.	Prototype Radiometer (142 GHz-172 GHz)	1 Receiver of Frequency (GHz): 142- 170 Frequency resolution: 1 GHz Noise Temp: < 5 eV Total no. of channels= 16 (fixed), 2 tuneable channels with bandwidths tuneable between 150-250 MHz for high frequency resolution measurements
109.	Radiometer	4 Receivers of Frequency (GHz): 122-138, 141-168, 172-200, 205-230

		<p>Frequency resolution: 1-2 GHz Noise Temp: <5 eV Total no. of channels= 58 (fixed), 16 tuneable channels with bandwidths tuneable between 150-250 MHz for real time measurement</p>
110.	Fourier Transform Spectrometer	<p>Spectral range: 70 GHz –1000 GHz, Frequency resolution \leq 5 GHz Linear path scan: \geq 40 mm Scanning repetition rate: \leq 20 ms Instrument's Etendue: $> 4 \times 10^{-5}$ m²sr Instrument's transmittance for Spectral range 70 GHz – 1000 GHz: \geq 70 %</p>
111.	Transmission Line including Quasi-optical systems	<p>1.Waveguide sections: Material: Aluminium 6061 T6 Alloy ID: 72 \pm0.05 mm, OD: 88\pm0.5, Inner surface finish: 7.5 micron Ra Ellipticity,WG tube inner surface:< 0.1mm 2. WG couplings: Alignment tolerance \leq \pm0.5 mm Alignment tolerance \leq 0.04 deg Vacuum seal: Helicoflex seal 3. Miter bends : WG Inner tube diameter: 72 \pm0.05 mm WG Outer Diameter (mm): 88\pm0.5 Waveguide axis bend angle, input port to output port (deg) 90° \pm 0.05° Mirror surface alignment to each WG axis: 45° \pm 0.04° deg Inner surface finish(Mirror/waveguide): 3-micron Ra/7.5 micron Ra 4. Polarization and Power splitter units - Ellipsoidal and plane mirrors, wire grid polarizer and beam splitters, higher order and cross polarized mode loss > 30 dB</p>
112.	Captive Supports and TL components	<p>Lateral Girder: Qty 3, made of 2 X C-channel, D-UPN100 , welded along the length in three positions by a spacer. Length is 2.7m Material: S335JR-DIN EN10025 2.Clamps, Qty: 15 for DN 150, 12 for OD 88, Material: S335JR-DIN EN10025 3.Vertical support: made of 1 X I-beam, HEB-100, welded to a square plate, and a circular, machined plate on either end, Welds from plates to I-beam are along all edges, Qty: total 6 (2 for each support, Material: S335JR-DIN EN10025, 4.Circular plate with 3 tabs,</p>

		Material: S335JR-DIN EN10025, Welds from tab to plate are along all edges, Qty: 6 5.Tubing: 4 * OD 88 Al6061 tubes-Length: 3000mm, 200 DIN Schedule 40 316LN tubing-length 3000m
113.	Windows	Qty: 8, Clear Aperture: 72mm, Pipe size: 88mm(OD), 72mm (ID), Material: Quartz, Metallic Seal, Thickness: 5.4 mm
114.	Two pilatus in vacuum detectors	1. Scope of work: Supply of in vacuum pilatus3 detectors along with accessories .2) No of detector module : 1, Approximate size : 88mm X34 mm, pixel size : 0.172 mm, Energy range : 2.7 keV to 18 keV, Frame rate : ~20 fps , Count Rate : ~1X10 ⁷ (photon/s/pixel), Cooling : water cooled detector head and Energy calibration : K-alpha lines of Cr, Mn, Cu, Ga, Mo and Ag.
115.	High quality Quartz and Silicon detectors	1.Scope of work : Supply of high quality spherical crystals 2. Crystal material : Quartz, Interplanar distance (2d) = 4.91304 Angstrom, Crystal cut : (11-20), Radius of curvature : ~1100 mm, Length : 50 mm and Height : 20 mm , Substrate material : BK 7 optical glass
116.	Be window	1.Scope of work : Supply and integration of Be window in an ITER-Style flange 2. Be foil thickness : 200 micron, shape : 40X90 mm, 3. Meshed honey comb SS grids to hold the window 4. Double walled flange assembly.
117.	Single module Pilatus 3 (qty 1)	Single Pilatus3 module, active area ~84mmX34mm, mountable inside HV chamber, pixel size 172 micron, high count rate capability ~ Mcnts/sec, high frame rate 100 fps, high quantum efficiency over 2 - 13 keV. Scope of supply includes detector head, detector electronics, detector server, cooling unit, power supplies, cables and connector, and all standard /optional accessories required for detector operation both in-air and in-vacuum, energy calibration.
118.	Bent crystal (qty 2)	X-ray quality crystal in elleptical configuration curved in a metal frame or optical contacted, high ecentricity ~0.98, length 120mm and height 20mm, material: silicon and germanium, crystal cuts: [111], [422],

		Scope of supply includes ready to mount crystals in a carry case and reports of tests performed
119.	Si detector with MCA (qty 1)	Silicon pin sensor active area ~25 sqmm, energy resolution 120-150 eV, working energy range from 1000 KeV to about 50 KeV, finger length 120mm, Scope of supply includes detector head, digital pulse processor, multi channel analyser, power supply, cables and connector, vacuum feed throughs, all standard/optional accessories and energy calibration.
120.	Fast SDD with MCA (qty 1)	Single drift sensor, active area ~30 sqmm, energy resolution 120-150 eV, working energy range from few 100 eV to about 50 KeV, finger length 120mm, Scope of supply includes detector head, digital pulse processor, multi channel analyser, power supply, cables and connector, vacuum feed throughs, all standard/optional accessories and energy calibration.
121.	Manson x-ray source (qty 1)	Wattage ~30W, High photon flux output ~100 Gph/sec/steradian, beam size upto 35x40sqmm, Long life filament electron source, multiple selectable targets generating characteristic lines in 0.1 to 13 KeV (materials: Al, Si, Mn, Ni, Mo, Ti, Zn, Ag, Rh, Pb) on a carousel, CW output, built on DN150 UHV vacuum cross, radiation hard motors, with beam monitoring Scope of supply includes complete X-ray source, filament and HV power supply, power supply and controllers of motorised stages, built-in SDD detector and control/data acquisition software. Test reports demonstrating x-ray beam stability few % and operation without maintenance needs for over 2 years
122.	TMP station with valves, gauges (qty 2)	Combined assembly of TMP and backing pump with digital controller, Display of vacuum level, vent valve, speed upto 300 l/s
123.	Pure targets (qty 10)	Purity over 99.9%, length 50mm and width 10mm, thickness ~mm, materials: Al, Si, Mn, Ni, Mo, Ti, Zn, Ag, Rh, Pb
124.	X-ray filters (qty 5)	length & width upto 100mm/100 mm diameter, purity over 99.9%, thickness ~few micron, materials:Al, Be, Mo, Ta etc.

125.	Rad-sources (absolutely calibrated) (qty 14)	Disk type, radio nuclides giving photon emission in 0.1 to 50 KeV, Strength ~20 micro curie, uncertainty 5 -10%, avg half life ~ year
126.	Image plate monitor	Digital X-ray film with electronic data readout, 100x100mm active area
127.	Low energy prototype	Single spectral channel (MLM/ pathalate) diffracting to a CCD detector, bent crystals in elliptical configuration, 120mm length and 20mm high, UHV chambers, crystal and detector on a single flange as per ITER spectrometer design. Scope of work/supply includes complete low energy spectrometer supply by down to component level manufacturing design, analysis and drawings, construction, assembly, testing, and delivery to ITER-India
128.	ITER X-ray spectrometer (qty)	Seven spectral channels in two groups: three crystals diffracting photons to hybrid pixel detector and 4 crystals diffracting low energy photons on 3 CCD detectors, bent crystals in elliptical configuration, 120mm length and 20mm high, UHV chambers, In-line X-ray source for calibration consistency, Neutron-gamma shielding for radiation protection, Plant I&C for control and data acquisition. The spectrometer has 10m long, DN150 sight-tube (consisting two all metal gate valves, axial, gimbal bellow and baking jacket) connecting spectrometer to ITER machine (qualification as per RCC-MR). Scope of work/supply includes down to component level manufacturing design, analysis and drawings, complete spectrometer construction, assembly, testing, absolute intensity calibration of all the channels and delivery to ITER, France
129.	Refurbishment of the Beam Source components and Beam Line Components (RID and Neu) (post utilization at INTF, before supply to ITER as per loan agreement)	Refurbishment of the component (specification will be dependent on the type of refurbishment)
130.	Absolute Valve	The valve has a nominal bore diameter of 1,600 mm, rated to sustain a pressure differential of 0.1 MPa across the plate whilst maintaining a leak rate of less than 1×10^{-8} Pam ³ /s

131.	Fast Shutter	A fast shutter (diameter ~1.6m) (opening and closing time 1s) is located downstream of the calorimeter, at the exit of the vessel. The design concept foresees the movement of a door perpendicular to the horizontal axis of the vessel. Sealing is provided via a flexible metallic seal. The Primary Vacuum Boundary of the Fast Shutter housing and top flange must have a leak rate better than 10 ⁻⁹ mbarl/s He.
132.	Metal Seal for Vessel	Spring Energised metallic seal of size ~9m x 5m with interspace pumping requirements (designed by Technetics and certified by IO and propriety)
133.	RF Generator for INTF	200 kW, 1 MHz RFG with automatic frequency tuning facility
134.	Exit scraper	Manufacturing, assembly, testing and supply of Exit scraper with overall height of ~2m . To be manufactured from CuOF panels (size of ~1.5m x 1m) involving the deep drilling, ED / brazing and EB welding.
135.	High Voltage Bushing	Manufacturing, assembly, testing and supply of 100kV high voltage bushing with overall diameter of ~1.5m. PIC component, involving metallic and non-metallic materials like large size Ceramic ring (along with its brazing with Kovar), FRP ring (along with its connection with SS), complex assembly of piping, Electrical, RF, Diagnostic feed throughs.
136.	Drift Duct Bellow	Manufacturing, assembly, testing and supply Drift Duct bellow, double walled with diameter of ~2m. RCC-MR / EN class double walled large size bellow, with stringent requirements on the movements, manufacturing design, welding configurations and fatigue testing requirements
137.	High Power Gyrotron Source Set (1MW of RF power at 170 GHz frequency) ; Qntty 2 sets	High Power Gyrotron Source Set (1MW of RF power at 170 GHz frequency) ; Qntty 2 sets
138.	Specialized Controllers , Instrumentation and power supplies	Specialized Controllers , Instrumentation and power supplies
139.	Temperature sensors (CERNOX and PT-100) Qty. 20	Specifications: Cernox: Measurement Range - 1-300K Accuracy - 4mK at 4.2K Calibration - At each temperature point

		<p>Annual drift - 20mK (<100K)</p> <p>PT-100:</p> <p>Measurement Range - 14-300K Accuracy - 100mK at 77K Calibration - At each temperature point Annual drift - 50mK (>77K)</p> <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of sensors 2. Supply of Calibration report
140.	Temperature sensor (Carbon-Ceramic)	<p>Specifciation:</p> <p>Carbon Ceramic:</p> <p>Measurement Range - 1-600K Accuracy - 4mK at 4.2K Calibration - At each temperature point Annual drift - 20mK (<100K)</p> <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of sensors 2. Supply of calibration reports
141.	Temperature transmitters Qty. 10	<p>Specification:</p> <ol style="list-style-type: none"> 1. Sensor types: Any cryogenic sensor 2. Output: Fieldbus 3. Accuracy: ~5mK at 4.2K
142.	Cryogenic accessories (Tapes etc.) Qty. 2 set	Should be compatible for operation at cryogenic temperatures with requisite adhesive strength.
143.	Mass flow meters (Orifice / Venturi / Coriolis type) Qty.: 1 of each type	<p>Specification:</p> <p>Quantity to be measured: Volumetric/Mass flow Type: Differential pressure/Frequency Range: 0 to 300 g/s (based on requirement) Operation temperature: 4.2K to 300K Accuracy: <5% of mass flow reading Flow turndown: Better than 10</p> <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of mass flow meters according to

		<p>applicable standards</p> <p>2. Calibration reports and manuals</p>
144.	Thermal mass flow meter Qty: 2	<p>Specification:</p> <p>Type: Capillary type Accuracy: <1% of mass flow reading Range: 0 to 35 g/s (Helium)</p> <p>Scope of work:</p> <p>1. Supply of mass flow meters 2. Calibration reports and manuals</p>
145.	Control valve controller Qty: 3	<p>Specification:</p> <p>Input: 4-20mA Output: Regulated air pressure for actuator control Local Display: should be available Position feedback: optional</p> <p>Scope of work:</p> <p>1. Supply of positioner 2. Installation</p>
146.	Dewar Level probe and transmitter Qty: 1	<p>Specifications:</p> <p>1. Type: Superconducting Type 2. Purpose: Liquid helium level measurement 3. Probe length: Depending on requirement 4. Accuracy: <1% of measured value 5. Output: 4-20mA</p> <p>Scope of work:</p> <p>1. Supply of probe and transmitter 2. Installation and maintenance manual</p>
147.	Oil separator 1 Level Qty: 3	<p>Model No. or type Description: Bekomat 12 (level Switch) Manufacturer: Bekomat Working pressure (min) in bar: 0.8 Working pressure (max) in bar: 16 Connection (inlet): 2xG 1/2 Connection (outlet): 1xG 3/8 Hose di: 10-13 mm Peak compressor Performance (m³/min): 8 Type of level sensor: Capacitiv</p>
148.	Instr. Air Service Unit Pressure Qty: 2	<p>Specifications:</p>

		<ol style="list-style-type: none"> 1. Input pressure: 0-20 bara 2. Output pressure: Configurable
149.	Vacuum gauge Qty: 05 Nos.	<p>Specification:</p> <ol style="list-style-type: none"> 1. Measurement Range: 10(-8) to 1000 mbar 2. Type: Pirani and combination guage 3. Accuracy: <15% of reading 4. Output: 0 to 10V <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of vacuum gauges 2. Test Certificates
150.	Pressure transmitter Calibration pressure source Qty: 05	<p>Specification:</p> <ol style="list-style-type: none"> 1. Type: Piezo resistive type 2. Range: 0 to 32 bara 3. Output: 4-20mA 4. Accuracy: 0.1% of reading <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of pressure transmitters 2. Calibration reports
151.	Dewar heater cartridge temperature	<p>Specification:</p> <ol style="list-style-type: none"> 1. Type: Thermocouple type 2. Accuracy: 0.5C of reading 3. Installation: Surface mount <p>Scope of work:</p> <ol style="list-style-type: none"> 1. Supply of sensors 2. Installation
152.	PLC , softwares and other electrical accessories Qty: 01	<p>Specification (software):</p> <ol style="list-style-type: none"> 1. Software: Simatic Step-7 2. Add on Module: CFC, Graph 3. HMI software: WinCC <p>Scope of work (software):</p> <ol style="list-style-type: none"> 1. Supply of software and licenses <p>Specification (PLC):</p> <ol style="list-style-type: none"> 1. PLC CPU: S7-400 series 2. PLC communication module: CP- 443-5

		<p>3. Power supply modules 4. AI/AO/DI/DO modules</p> <p>Scope of work (PLC):</p> <p>1. Supply of hardware in a DIN rail 2. Manuals</p>
153.	Control valves Qty: 05	<p>Specification:</p> <p>1. Size: As per requirement (DN10 to DN80) 2. End switches 3. Actuator: Single effect (Pneumatic) 4. Bellow sealed 5. Leak rates: 10(-6) mbar-l/s or better</p> <p>Scope of work:</p> <p>1. Supply of control valves 2. Installation</p>
154.	Vacuum pump and Helium leak detector spare parts Qty: 01	rotary type or turbomolecular (to evacuate the chamber)
155.	Multi layer insulation (MLI) Qty: 01	silver Aluminized mylar (to mitigate the radiation heat load)
156.	Cryocooler (GM type - 2 stage) Qty: 01	<p>Specification:</p> <p>1. Type: G-M type 2. 2nd stage temperature: 1.5W at 4.2K 3. Compressor and cooling water connectors</p>
157.	Pressure transmitter	<p>Specification:</p> <p>1. Type: Piezo resistive type 2. Range: 0 to 10 bara 3. Output: 4-20mA 4. Accuracy: 0.1% of reading</p> <p>Scope of work:</p> <p>1. Supply of pressure transmitters 2. Calibration reports</p>
158.	Arc-4 (4Nos.) with cable (if inhouse arc detector could not perform as per requirement)	Arc 4 with 16 channel, standard item of AFT
159.	Cables for IO compatible (prototype only)	Different categories of cables

160.	SSPA (18 Nos.) (if inhouse developed SSPA could not perform as per requirement)	output power 10kW, 35-65 MHz, Input power 1mW
161.	3dB Combiner (9Nos.) (if inhouse developed 3dB Combiner could not perform as per requirement)	Input power 1.5/1.7MW, Output Power 2.5/3 MW, 35-65 MHz, Fixed.
162.	200kW Dummy Load for 3dB combiner (9Nos)	Power handling 200kW 35-65 MHz
163.	Fast Controller PC	Standard item
164.	PLC with I/O board	As per ITER Organisation catalogue
165.	Motor & controller with accessories (36 sets)	As per ITER Organisation catalogue
166.	SARAL Rack	As per ITER Organisation catalogue
167.	PXI/cRIO system with I/O board	As per ITER Organisation catalogue
168.	Halogen free fire retardent multi core Fiber optic cable	As per ITER Organisation catalogue
169.	RF synthesizer & other RF component	9kHz to 1 GHz, power output -20dBm to +13 dBm
170.	High voltage Probe - 20 No.	Max voltage: 150kV, DC/Pulsed, divider ratio:10000:1 , cable length: 10ft with BNC connector, Accuracy: +/- 0.5%, Conformity certificate according to IEC 61010-1
171.	Current Sensor - 20 No.	Frequency: DC to 5MHz, current: 10A to 150A, o/p connector:BNC, Size: Approx 4x4Inches, weight: less than 700gm
172.	Cooling water Instrumentation: sensors with signal conditioner - 17 sets	Parameters to measure: water temperature, flow, pressure, conductivity. O/p voltage/current compatible with PLC
173.	Control valves for water line - 10 Nos.	1/2 inch, butterfly valve with electrical actuator
174.	Flexible hoses with QRC - 50 sets	Non-conductive hydraulic hose with quick release couplers at both ends required for active cooling of AC/DC converter modules. Core tube material: Polyester elastomer, Cover material: Polyurethane.
175.	Air purifier and compressor - 1 nos	1000 CFM, 6 bar compressor unit with air purifier
176.	Gas feed control valve - 1 nos	Needle valve for fine control of fluid flow
177.	Magnetic snubber with Thermoplastic Casing - 15 nos	Nanocrystalline soft magnetic material core in circular form with thermoplastic casing
178.	CRIO system - 2sets	i. Bus connector: MXI Express X1 interface based on PCI Express ii. No. of slots: 14 iii. 32-channel, 7µS, digital I/O with DSUB connector, iv. MXI -Express Cable

179.	EMC Compitable cubicle - 9 nos	EMI/EMC compatible cubicle mainly to house instrumentation. Preffered with standard dust filter, fans, temperature sensors and position sensor, heigh \geq 42U
180.	Industrial computer - 3 nos	Standard industrial computer for data acquisition and data storage, preffered with latest model/ technical specs
181.	8- core plastic Fiber Cable - 5000m	No. of core:8, Jack material: Polymer, Compatible with Avago Versatile Link Family of connectors and fiber optic components, Diameter: 1mm
182.	Industrial Workstation - 1 nos	Standard industrial work station for data storage, preffered with latest model/ technical specs to be used in control rooms for various phsics experiments
183.	DC Disconnecter - 35 nos	Air insulated, Indoor, off load operation, non enclosed disconnecter with and without earth bar. Rated voltage: 22kV, 50Hz, Rated current : 110A[min], Rated short circuit current: 5kA[min], No of pole : Two pole, Operating mechanisim: Motorized, Deviec mounted. Compliance with IEC 62271-102
184.	High Voltage Relay - 2 nos	Air insulated HV relay, non enclosed, Pole configuration: 2 Pole NO contact and 2 Pole DT contact, Continuous working voltage : 35kV DC, Continuous current : 5A [min], Mounting position: Horizontal, Operating mechanisim: Motor or solenoid based, 230V, 50Hz, Auxiliary switch : 2 Nos [NO/NC/SPDT] per position
185.	High current power supply - 2 nos	1. 15V, 4kA, and 30V, 600A current: settable for 20% to 100%, Accuracy: 2%, Current resolution: 100A
186.	22kV Input cable-1000 mtr	Rated voltage 12/20/24kV, 95 cross section,class-2 copper conductor, XLPE insulation, single core cable, halogen free, low smoke
187.	Output DC coaxial cable with screen - 1000 mtr	Rated voltage 18/30/36kV, 95 cross section,class -2 copper conductor,helical copper wire screen lapped with copper tape having 35mm 2 cross section [min],copper tape outer screen, XLPE insulation, single core cable, halogen free, low smoke
188.	LV cable -3000 mtr	0.6/1/1.2kV, 25 cross section, class 5 copper conductor, silicon/EPR insulation,halogen free, low smoke single core cable

189.	Control cables - 1000 mtr	0.6/1/1.2kV, 2.5 cross section, class 5 copper conductor, EPR/HEPR insulation, multi-core, thermoplastic sheath, halogen free, low smoke
190.	RF (Radio frequency) lines - 600m	3½" coaxial line, RF frequency: 1MHz, Length: 600m
191.	RF Connectors - 200 nos	Connectors for 3½" coaxial line
192.	Butterfly type valves	Pneumatic operated butterfly valves of sizes from DN 150 to DN 600; pressure rating vary from 150# to 900#. Classifications as per ITER: QC-1, SC-1 (SF), SIC-2, Design temperature upto 270 degC. Qualification through shake table test